



KENT P2 - Type 2 IGU

The Kent Paver in Ground Power Unit, **KIGU- 450/600 Type 2** is an ideal product for trading areas, open air areas with events and exhibitions where temporary power is required. This model, Type 2 has a 450mm x 600mm top recessed cover.

It contains an IP67 electrical panel that holds a combination of up to four sockets either 16 Amp or 32 Amp 1 Phase. Alternatively, it can hold a smaller IP67 electrical panel with two sockets plus an additional data panel with up to four RJ45 data points. For added safety the lids can be closed during operation, this setting requires a 450mm depth to allow for plug in space. There is also an option for a shallow unit that has a 320mm depth. However, this depth restricts the unit to use only in the open position.

The hinged recessed cover ensures the units are unobtrusive when not in-use. The In Ground Power Units are manufactured in accordance with FACTA and BS EN124 standards. The covers are suitable for all types of paving blocks and are manufactured to meet required loadings. They are fabricated in grade 316 stainless steel as standard.



Product Code	Visible Frame Size	Unit Depth	Cable Duct (Ø)
KIGU 450/600	450mm x 600mm	450mm	125mm
KIGU 500/600-3Ph	500mm x 600mm	500mm	125mm

- Features**
- ❑ Gas Rams
 - ❑ Up to 4nr IP67 rated sockets
 - ❑ Slam lock
 - ❑ Suitable for market trading areas
 - ❑ 110mm diameter outlet point

- Designed for**
- ❑ 2nr 32 Amp 1 Phase sockets with 4nr RJ45 data points or
 - ❑ 2nr 32 Amp 1 Phase sockets plus 2nr 16 Amp 1 Phase sockets or
 - ❑ 2nr 32 Amp 3 Phase (500mm deep unit)

- Other Options**
- ❑ 4nr 16 Amp 1 Phase
 - ❑ 3nr 32 Amp 1 Phase



44 Ton Truck
FACTA B Loading
EN124 B125 Loading

Specify Kent IGU– Type 2; KIGU 450/600; 450mm x 600mm top ; with a 450mm depth (Closed Use); Grade 316 Stainless Steel; 2nr 32 Amp 1 Phase; 4nr RJ45 Data



KENT P2 - Type 2 IGU



Use this box for Food Carts connecting cooking equipment.
Can have 32 Amp 3 Phase Power for heavy use.

