



KENT P3 - Type 3 IGU

The Kent Paver in Ground Power Unit, **KIGU- 600/600 Type 3** is an ideal product for trading areas, open air areas with events and exhibitions where temporary power is required. This model, Type 3 has a 600mm x 600mm top recessed cover.

It contains an IP67 rated electrical panel that holds a combination of 3 or 4 sockets either 16A, 32A or 63amp Single Phase or Three Phase sockets. An additional data panel with 1 to 4 RJ45 sockets can also be added to this unit along with the sockets. For added safety the lids can be closed during operation, this setting requires a 450mm depth to allow for plug in space. There is also an option for a shallow unit that has a 320mm depth. However, this depth restricts the unit to use only in the open position.

The hinged recessed cover ensures the units are unobtrusive when not in-use. The In Ground Power Units are manufactured in accordance with FACTA and BS EN124 standards. The covers are suitable for all types of paving blocks and are manufactured to meet required loadings. They are fabricated in grade 316 stainless steel as standard.



Product Code	Visible Frame Size	Unit Depth	Cable Duct (Ø)
KIGU600/600	600mm x 600mm	450mm	125mm
KIGU600/600-3Ph	600mm x 600mm	500mm	125mm
KIGU600/650-63A	600mm x 650mm	650mm	125mm

Specify Kent IGU– Type 3; KIGU 600/600; 600mm x 600mm top ; with a 450mm depth (Closed Use); Grade 316 Stainless Steel; 2nr 16 Amp 1 Phase & 2nr 32 Amp 3 Phase Sockets; 4nr RJ45 Data

Specify Kent IGU– Type 3; KIGU 600/600(500)-3Ph; 600mm x 600mm top ; with a 500mm depth (Closed Use); Grade 316 Stainless Steel; 2nr 16amp 3 Phase & 1nr 32amp 3 Phase Socket; 4nr RJ45 Data

Specify Kent IGU– Type 3; KIGU 600/650(650)-63A; 600mm x 650mm top ; with a 650mm depth (Closed Use); Grade 316 Stainless Steel; 1nr 63amp 3 Phase

- Features**
- ❑ Mechanical Rams
 - ❑ Up to 4nr IP67 rated sockets
 - ❑ Slam lock
 - ❑ Suitable for market trading areas
 - ❑ 110mm diameter outlet point

- Designed for**
- ❑ 3nr 32 amp + 4nr RJ45 Data or
 - ❑ 2nr 32a + 2nr 16a + 4nr RJ45 Data

- Other Options**
(Limits sockets to two)
- ❑ RJ45 Datapoints
 - ❑ XLR Audio Connection



44 Ton Truck
FACTA B Loading
EN124 B125 Loading



KENT P3 - Type 3 IGU



Deeper version can take 32 Amp 3 Phase Power.
A slightly larger variation is our smallest box that can take 63 Amp 3 Phase power.

